



耐特 NYTEX COMPOSITES CO., LTD.
耐特科技材料股份有限公司

TEL:02-26963366 FAX:02-26963399
<http://www.nytex.com.tw>

产品资讯

Product Information

NYLOY® D-0700N

• PC/ABS • 耐冲击级 • 本色

性质	PROPERTY	测试方法 METHOD	单位 UNIT	结果(数据) RESULT
机械性能	MECHANICAL			
抗张强度	Tensile Strength	ASTM D638	kg/cm ² (MPa)	510 (50.05)
断裂伸长率	Elongation	ASTM D638	%	35
抗折强度	Flexural Strength	ASTM D790	kg/cm ² (MPa)	790 (77.53)
抗折弹性系数	Flexural Modulus	ASTM D790	kg/cm ² (MPa)	2.20 x10 ⁴ (2158.98)
冲击强度	IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm (J/M)	52 (509.8)
	IZOD Impact, Notched 1/8" -20°C	ASTM D256	kg-cm/cm (J/M)	35 (343.14)
硬度	Hardness Rockwell R Scale	ASTM D785	-	-
	Hardness Shore D	ASTM D2240	-	D-82
热性能	THERMAL			
热变形温度	Heat Deflection Temp	ASTM D648		
	(18.6kg/cm ²) (1.82MPa)		°C	-
	(4.6kg/cm ²) (0.46MPa)		°C	125
其他性能	OTHER			
密度	Density	ASTM D792	g/cm ³	1.14
模收缩率	Mold Shrinkage	ASTM D955		-
	横向	Normal	%	0.65
	纵向	Parallel	%	0.54
含水率	Moisture Contents	-	%	-
附注	REMARK			
(1) 本物性表为典型测试值, 仅供参考, 不作为正式质保承诺。				