



耐特 NYTEX COMPOSITES CO., LTD.
耐特科技材料股份有限公司

TEL:02-26963366 FAX:02-26963399
<http://www.nytex.com.tw>

产品资讯

Product Information

NYLOY® D-0700N

● PC/ABS ● 耐冲击级 ● 本色

性质	PROPERTY	测试方法	METHOD	单位	UNIT	结果(数据)	RESULT	
机械性能	MECHANICAL							
抗张强度	Tensile Strength	ASTM D638		psi		7254.62		
断裂伸长率	Elongation	ASTM D638		%		35		
抗折强度	Flexural Strength	ASTM D790		psi		11237.55		
抗折弹性系数	Flexural Modulus	ASTM D790		psi		312944.52		
冲击强度	IZOD Impact, Notched 1/8" 73.4°F	ASTM D256		ft-lb/in		9.54		
		ASTM D256		ft-lb/in		6.42		
硬度	Hardness Rockwell R Scale	ASTM D785		-		-		
		ASTM D2240		-		D-82		
热性能	THERMAL							
热变形温度	Heat Deflection Temp	ASTM D648						
				264 psi	°F	-		
				66 psi	°F	257		
其他性能	OTHER							
密度	Density	ASTM D792		lb/in ³		0.0353		
模收缩率	Mold Shrinkage	ASTM D955				-		
				横向	Normal	%	0.65	
				纵向	Parallel	%	0.54	
含水率	Moisture Contents	-		%		-		
附註	REMARK							
(1)本物性表為典型測試值，僅供參考，不作為正式質保承諾。								