



NYTEX COMPOSITES CO., LTD.

TEL:02-26963366 FAX:02-26963399
http://www.nytex.com.tw

NYLOY[®] KF-0030N 313WLT

• Nylon • Insulated Thermal Conductive Flame Retardant • White

Product Information

PROPERTY	METHOD	UNIT	RESULT
MECHANICAL			
Tensile Strength	ASTM D638	kg/cm ²	620
Elongation	ASTM D638	%	1.4
Flexural Strength	ASTM D790	kg/cm ²	1150
Flexural Modulus	ASTM D790	kg/cm ²	82000
IZOD Impact, Notched 1/8" 23°C	ASTM D256	kg-cm/cm	3.0
THERMAL			
Heat Deflection Temp (4.6kg/cm ²) (0.46MPa)	ASTM D648	°C	200
Conductivity Through-plane In-plane	ASTM E1461	W/m*K	1.3
ELECTRICAL			
Surface Resistance	ASTM D257	Ohm-P-SQ	>1E+12
OTHER			
Density	ASTM D792	g/cm ³	1.78
Mold Shrinkage // flow ⊥ flow	ASTM D955	%	0.4 0.6
Flammability	UL-94	3.2mm	V0
REMARK			
(1)This data is for reference only.			